



Section 5.0

Requirements Overview



Outline



- Requirements Definition
- Requirements Tree
- Requirements Document
- Requirements Criticality
- Key Requirements



Requirements Definition Approach




- High level requirements defined in the Science Requirements (Level 1) Document and the Mission Systems Specification (Level 2)
- Context provided by the Operations Concept Document
- Requirements (Level 3) for ground system defined in the Ground System Requirements Document (GSRD)
 - Comprised of System-level requirements that apply to multiple or all elements, and requirements for each ground system element
 - Includes: SN, GN, Communications, MOC, FDF, LAT IOC, GBM IOC, SSC, HEASARC, GCN, Spacecraft I&T Facility, KSC
 - Will also be entered into Project's Requirements Data Base (DOORS)
- These represent the set of requirements that will drive the Ground System Test Program
- Each element will have a set of element-level (Level 4) requirements that will trace to the GSRD
 - IOC's will also trace to other documents for their role in instrument I&T
 - GSSC has science support requirements that trace directly to the SRD and MSS, and that are driven by the Project Data Management Plan (PDMP)



Requirements Tree







Ground System Requirements Document



- GSRD is organized by element/function
 - System applies to three or more elements
 - Element such as SN, MOC, GSSC, LIOC, FDF
 - Each section organized by subtopics
 - Example for MOC: Facility, Security, RMA, Interface, Planning & Scheduling, Telemetry & Command Processing, Data Processing, Offline Processing, Automation, Support
- Requirements documented in table format to facilitate conversion to a verification matrix, with columns for:
 - Requirement Number
 - Requirement Text
 - Requirement Clarification/Comment
 - Requirement Trace (Source and Source ID)



Requirements Criticality



- Ground system functions that are launch critical have been documented in the GSRD
 - Helps to ensure that while the entire ground system is being designed, implemented and tested before launch, there is a mechanism to focus priorities on what is required for launch if necessary (e.g., prioritizing discrepancies)
 - Launch critical means that the capability is required in order to launch the observatory (i.e., support launch and early orbit activation and achieve some basic science)
- Requirements in GSRD will be assigned a "launch criticality" indicator based on if they apply to a function that is considered launch critical
- Launch criticality will be assigned in the GSRD Requirements
 Verification Matrix (under GS CCB control)



Launch Critical Functions



- Provide ground station X and S-band and SN S-band communications with the observatory
- Acquire, receive and archive observatory science and housekeeping data
- Process and display observatory housekeeping data
- Recognize, identify, and log observatory alarm conditions
- Perform observatory engineering analysis
- Generate and uplink real-time observatory commands via command scripts
- Generate and uplink observatory stored command loads
- Dump and manage recorded observatory housekeeping and science data
- Generate and uplink observatory memory loads
- Initiate and process observatory memory dumps
- Perform Level 0 processing on observatory science and HK data



Key Requirements



- Support highly autonomous mission operations that enables lightsout operations approach
 - Automated pass operations (including SSR dumping)
 - Automated data handling/processing
 - Automated telemetry monitoring, alarm detection, and operator paging
 - Support operators with remote access to data/displays
- Generate science data products (Level 1) within 72 hours of initial detection on-board by instrument
 - 36 hours space to ground
 - 12 hours ground station to LAT IOC (through MOC)
 - 24 hours for LAT IOC to generate Level 1 products
- Provide ability to support science observation planning, and to translate this planning into on-board activities/commands
- Provide Burst Alerts from spacecraft to GCN within 7 seconds
- Provide ability to respond to TOO Requests within 6 hours



Key Requirements



- Support CCSDS for telemetry (Series 100 Blue Books) and command (Series 200 Blue Books) data
- Capture 98% of the science and housekeeping data
- Ensure ground system meets NASA IT Security requirements (i.e., must be NPG 2810.1 compliant



RMA Requirements



- Provide reliability of .9998 for ground system components supporting critical real-time operations
 - Applies to SN, GN, Ground Communications, MOC
- Provide ability to fail over to a backup system within 1 minute for ground system components supporting critical real-time operations
- Provide ability to bring failed prime system back online within 12 hours of for ground system components supporting critical real-time operations
- Ensure no single point of failure exists for for ground system components supporting critical real-time operations